

## KVS-E101 Front Touch Numblock

Rugged keyboard made of stainless steel with integrated touchpad for front panel mounting.



## Description

This keyboard is constructed of a stainless steel frontplate with an integrated [Touchpad](#) for frontpanel mounting, which is facilitated by the studs on the backside of the keyboard.

Due to its ruggedness and its IP65 / NEMA 4 rating of resistance against liquids and dust this keyboard can even be used for outdoor purposes.

This keyboard has an integrated touchpad with 2 keys instead of the NUM-block. This saves a lot of space and the touchpad is close to the rest of the keyboard. There are no mouse keys located on the keyboard. The clicking is done by simply tipping on the surface of the Trackpad.

If the NUM-block is needed, there is another version of this keyboard, that has the touchpad integrated instead of the arrow keys. You can find the other keyboard [HERE](#)

Like the other keyboards of the fullsize-range this keyboard is water- and dust proof to IP65.

As backpanel mounted version this keyboard can be easily integrated into an existing housing.

For further information you can go to the [main page](#) of this keyboard range.

**Specification****Mechanical data**

Housing: High-Grade Steel  
 Degree of Protection: IP65  
 Dimensions: 145,4 x 449 x 29 mm  
 Cable Length: 180 cm

---

**Keys**

Key Technology: membrane  
 Number of Keys: 105  
 Keyboard Layout:  
 Operational Life: 10 mio. keystrokes min.  
 Stroke Force:  $0,9 \pm 0,1$  N  
 Stroke Travel:  $1,6 \pm 0,1$  mm  
 Key Legend: Laser

---

**Electric Data**

Interface: [PS/2](#)  
 Additional Interface: PS/2

---

**Environment**

Operating Temperature: from 0 °C to +60 °C  
 Storage Temperature: from -20 °C to +70 °C

Order No.	Article	
KV1204	KVS-E101-F-Touch-PS/2-Ger	PS/2 interface, german layout
KV1378	KVS-E101-F-Touch-USB-Ger	USB, German
KV1205	KVS-E101-F-Touch-PS/2-US	PS/2 interface, US layout
KV1252	KVS-E101-F-Touch-PS/2-ES	PS/2 interface, spain layout

**sales@tastaturen.com Telefon: (0 81 42) 66 95 8-0 Fax: (0 81 42) 66 95 8-11**