



KVS-E105 Table-Top-Version

The table-top version of the KVS-E series



Description

Modern design and extreme ruggedness all in one!

Up to now the stainless steel keyboards of this series were only available as mountable versions. This keyboard in a table-top housing can now be used just as a standard keyboard without having to mount it.

The riser on the back of the keyboard slants the keyboard towards the user, making it much more ergonomic than any keyboard mounted flat into the desktop surface.

The sides of the keyboard can be ordered in one of the 8 standard colors:

Terracotta	RAL 2010
Red	RAL 3000
Magenta	RAL 4003
Blue	RAL 5013
Silver	RAL 9006
Anthrazit	RAL 9007
Black	RAL 7021

Keyboards can be ordered with customer specifically colored endcaps at no additional cost beginning with 25 pieces.

In addition to the design aspects these keyboards are extremely robust. Just as one expects it of metal keyboards they are water and dust proof to IP65 and withstand even hard blows, so they can easily be used in areas prone to vandalism.

For further information you can go to the [main page](#) of this keyboard range.

Specification**Mechanical data**

Housing:	Table-top housing
Housing:	High-Grade Steel
Degree of Protection:	IP65
Dimensions:	483,2 x 171,6 x 36,7 mm
Cable Length:	180 cm

Keys

Keyboard Layout:	Windows95-Country
Operational Life:	10 mio. keystrokes min.
Stroke Force:	0,9 ± 0,1 N
Stroke Travel:	1,6 ± 0,1 mm
Key Legend:	Laser

Electric Data



Interface:	PS/2 or USB
------------	---

Environment

Operating Temperature: from -20 °C to +70 °C

Order No.	Article	
KV1227	KVS-E105-Tisch-PS/2-Ger	PS/2 interface, german Laoyut
KV1229	KVS-E105-Tisch-PS/2-US	PS/2 interface, US layout
KV1230	KVS-E105-Tisch-Ger-USB	USB interface, german Laoyut
KV1231	KVS-E105-Tisch-US-USB	USB interface, US Laoyut

Links

Click!	Titel
	PI 061 - 03/11/2004 KVS-E Table Top Version Design Nuances for all Application Areas
	PressReview

sales@www.tastaturen.com Anrufen: (0 89) 89 43 99-0 Faxen: (0 89) 89 43 99-11